



BINGO BASE

- Timeless design
- Low weight
- Reflectors: 15D, 30D, 50D
- Available Drivers: ON/OFF for 1-phase
Global Track Base

PRINT CARD

Technical data

Input Power	LED-Module	Color Consistency	Installation Type	Material	Lumen Maintenance	Luminaire Color
-------------	------------	-------------------	-------------------	----------	-------------------	-----------------

220-240V	PHILIPS-SAMSUNG-CITIZEN	2-Step MacAdam	Nordic Aluminium Global Track Base	Powder Painted Die-Cast Aluminum	50 000h L80 B10	White (RAL 9016), Black (RAL 9005), Silver (ca RAL 9006)
----------	-------------------------	----------------	------------------------------------	----------------------------------	-----------------	--

COB Type	Forward current	System Luminous Flux	System Power	Lm/W
----------	-----------------	----------------------	--------------	------

CRI 90 3000K	200mA	990 lm	8,1 W	122.2
--------------	-------	--------	-------	-------

CRI 90 3000K	650mA	3 090 lm	25,4 W	121.6
--------------	-------	----------	--------	-------

CRI 90 3000K	850mA	3 936 lm	33,7 W	116.8
--------------	-------	----------	--------	-------

CRI 90 4000K	200mA	1 037 lm	8,1 W	128.0
--------------	-------	----------	-------	-------

CRI 90 4000K	650mA	3 265 lm	25,4 W	128.5
--------------	-------	----------	--------	-------

CRI 90 4000K	850mA	4 171 lm	33,7 W	123.8
--------------	-------	----------	--------	-------

